

REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD





SPECIFICATIONS


Electrical
- Current Rating: 35A
- Voltage Rating: 650V AC/DC
- Contact Resistance: 1mΩ Max
- Insulation Resistance: 1000 MΩ Min.
- Withstanding Voltage: 3000V AC/DC
- Temperature Range-Operating: -55°C~+125°C

Mechanical
- Durability: 500 Cycles

Material and Plating
- Housing: PBT (UL 94V-0) ,Black
- Pawl spring: Beryllium Copper

Applicable contact socket: F0CLCT-02384190-02

Applicable mounting screw: FSM040-10100200-01



Recommended Panel Layout

THIRD ANGLE PROJECTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY LEO	DATE 04/JUN/23	PART NO. F00MPC-P04SA350-02	ITEM NO. F00MPC	TXGA Building Technology Cornerstone
DESIGN UNITS mm	X. ±0.30	X.° ±5°	CHECKED BY GISELLE	DATE 04/JUN/23	TITLE Power Module Connector 4Circuits Plug 35A		REV 0 / SHEET NO. 1/1
SCALE 5:1 / SIZE A4	X.X ±0.20	X.X° ±2°					
	X.XX ±0.15	X.XX° ±1°	DRAWN BY PYD	DATE 04/JUN/23	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
	X.XXX ±0.10	X.XXX° ±0.5°					