
REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD





SPECIFICATIONS


Electrical
- Current Rating: 120A
- Voltage Rating: 1000V AC/DC
- Contact Resistance: 0.66mΩ Max
- Insulation Resistance: 1000 MΩ Min.
- Withstanding Voltage: 3000V AC/DC
- Temperature Range-Operating: −55°C~+125°C

Mechanical
- Durability: 500 Cycles

Material and Plating
- Housing: PBT (UL 94V-0) ,Black
- Contact Terminal: Brass / 1.5 μm Silver Plated
- Board Lock: Phosphor Bronze/ Tin plated







Recommended P.C.Board Layout

THIRD ANGLE PROJECTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY LEO	DATE 04/JUN/23	PART NO. F00MPC-S02RA1200-01	ITEM NO. F00MPC	TXGA Building Technology Cornerstone
DESIGN UNITS mm	X. ±0.30	X.° ±5°	CHECKED BY GISELLE	DATE 04/JUN/23	TITLE Power Module Connector 2Circuits Socket 120A		REV 0 / SHEET NO. 1/1
SCALE 5:1 / SIZE A4	X.X ±0.20	X.X° ±2°					
	X.XX ±0.15	X.XX° ±1°	DRAWN BY PYD	DATE 04/JUN/23			
	X.XXX ±0.10	X.XXX° ±0.5°					

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION