Product specification

1. Scope

This specification applies to the Power module connector, specifying the product's performance indicators, test methods and test requirements.

Applicable Product Models: F00MPC-P03SD350-01/F00MPC-S03RD350-01 / F0CLCT-02384190-01

2. Applicable Standards

In the event of conflict between the requirementsof this specification and the product drawing, the product drawing shall take precedence. In the event ofconflict between the requirements of this specification and the referenced documents, this specification shall take precedence.

3. Materials

Component		Material Specification	Color
Socket	Housing	PBT (UL94V-0)	Black
	Contact	Brass(1.5 μm Silver Plated)	-
Plug	Housing	PBT (UL94V-0)	Black
	Pawl spring	Beryllium Copper	-
Female Terminal	Socket Sleeve	Brass(1.5 μm Silver Plated)	-
	Crown Lamella	Beryllium Copper(1.5 μm Silver Plated)	-

4. Appearance and Dimensions

4.1 Appearance：The product surface shall be free from defects, dirt, cracks and mechanical damage. Contacts shall be free from rust, oxidation or plating peeling.

4.2 Appearance and dimensions shall comply with the requirements of product drawings.

4.3 Exchangeable: Exchangeable with same specification products.

5. Parameter Range

Parameter Name	Value & Unit
Rated Current	35A
Rated Voltage	650V AC/DC
Operating Temperature Range	-55 ℃ ~+125 ℃
Applicable Wire Gauge	14 AWG~10 AWG

6. Test Requirements and Procedures Summary

Serial No.	Item	Test Method	Technical Requirements
1	Examination of Product	Visual inspection	Meet the drawing requirements, no damage or abnormality in visual appearance
Electrical Requirement			
2	Dielectric Withstanding Voltage	Apply 3000V AC(rms)for I minute and the leakage current shall not exceed 1mA to the adjacent terminal and ground of the mate connectors	No flashover or insulation breakdown
3	Contact Resistance	Mate the connector, test with a low-power circuit	Contact Resistance ≤1mΩ
4	Insulation Resistance	Apply 500V DCfor I minute between adjacent contacts to measure the insulation resistance	Insulation Resistance ⩾1000MΩ
Mechanical Characteristics			
5	FemaleTerminal crimpingWire strength	Axial pull-out force of Femaleterminal crimped to wire	14AWG: ≥250N 12AWG: ≥400N 10AWG: ≥600N
6	Female Terminal Retention Forcet	Terminal and housing cavity mating, axial withdrawal along the axis	RetentionForce ≥98N
7	Single contact Withdrawal force	Axial pull-out force between mated male and female terminals	Withdrawal force:2.5N~6.5N
Environmental Performance			

8	Durability	Connector in assembled condition without environmental test, perform 500 mating and unmating cycles	Appearance: No damage; Contact Resistance≤1mΩ; Insertion Force≤2.5N~6.5N;
9	Sinusoidal Vibration	Waveform: Sine sweep. Frequency range: 10Hz ~2000Hz. Acceleration amplitude: 147 m/s² (15g). Sweep rate: 1 oct/min (octave per minute). Directions: Three orthogonal axes X, Y, Z, tested separately for each axis. Duration per axis: 120 min.	Appearance: Nodamage; CurrentDiscontinuity ≤1μs; Contact Resistance≤1mΩ;
10	Shock Test	Waveform: Half-sine wave. Peak acceleration: 980 m/s² (100g). Pulse duration: 6ms. Directions: X, Y, Z three axes, both positive and negative directions for each axis. Number of shocks: 3 shocks per direction.	Appearance: No damage; Current Discontinuity ≤1μs; Contact Resistance≤1mΩ;
11	Temperature	Mate the connector and measure the temperature rise of contacts at different current levels.	Refer to the attachment Figure 6.1
12	Steady-State Humidity Test	Test Temperature: 40℃±2℃, Relative Humidity: 98%±2% RH, Duration: 240h (10 days, Condition A).	Appearance: No damage; Contact resistance≤1mΩ; Insulation resistance≥1000MΩ; No flashover or insulation breakdown;
13	Temperature cycling	The connector under unmated condition is placed in a test chamber for temperature cycling test. Each cycle consists of exposure at -55±5℃ for 2 hours and 125±5℃ for 2 hours, total of 3 cycles. After test, the housing and contact assembly shall be free of deformation, cracks, plating peeling and other damages.	Appearance: Nodamage; Contact Resistance≤1mΩ;
14	Salt Spray	Salt concentration: 5%, temperature: (35±2) ℃, test time: (48±2) h; after the test, rinse residual salt with clean water, wipe dry	Appearance: no damage; Contact resistance≤1mΩ;

		before measurement	
15	Resistance to Soldering Heat	The connector plug is assembled on the PCB and passed through the soldering furnace. The temperature of furnace zone is set to 140℃, solder bath temperature is 265℃±5℃, chain conveyor speed is 1350 mm/60 s.	Appearance: no damage



Figure 6.1 Contact Temperature Rise vs Current Curve