




SPECIFICATION

Technical Parameters


Temperature range: $-40\sim+125^{\circ}\text{C}$;
 Characteristic impedance: 50Ω ;
 Frequency range: $\text{DC}\sim 6\text{GHz}$;
 Voltage Rating: 170V rms ;
 Dielectric withstanding voltage: 750V rms ;
 Insulation resistance: $\geq 1000\text{M}\Omega$;
 VSWR: $\leq 1.25(\text{DC}\sim 6\text{GHz})$
 Inner Conductor Contact Resistance: $5\text{m}\Omega \text{ MAX}$;
 Outer Conductor Contact Resistance: $2.5\text{m}\Omega \text{ MAX}$;

Mechanical

Durability: 500 cycles

Material and Plating

Insulators: PTFE(UL 94V-0), White
 Contact: Brass, 1μ " Gold plated
 Body: Brass, 1μ " Gold plated
 Snap Ring: Phosphor Bronze, 1μ " Gold plated



Recommended cable stripping dimension

 THIRD ANGLE PROJECTION		GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY LEO	DATE 04/JAN/22	PART NO. FOMMCX-P50POS0P-02	ITEM NO. FOMMCX	 Building Technology Cornerstone	
		X. ±0.30	X.* ±5°	CHECKED BY	DATE	TITLE			
DESIGN UNITS mm		X.X ±0.20	X.X* ±2°	GISELLE	04/JAN/22	MMCX Plug 180° Vertical For RG405&.086” cable		REV 0	SHEET NO. 1/1
SCALE 5:1	SIZE A4	X.XX ±0.15	X.XX* ±1°	DRAWN BY PYD	DATE 04/JAN/22	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
		X.XXX ±0.10	X.XXX* ±0.5°						

REV 0 SHEET NO. 1/1