

## Product specification

### 1. Scope

This specification applies to the Pitch 2.54mm Box Header connectors, specifying the product's performance indicators, test methods and test requirements.

Applicable Product Models: FBH25430 series.

### 2. Applicable Standards

In the event of conflict between the requirements of this specification and the product drawing, the product drawing shall take precedence.

### 3. Parameter Range

Parameter Name	Value & Unit
Rated Current	1A
Rated Voltage	300V
Operating Temperature Range	-40 °C ~+105 °C

### 4. Appearance and Dimensions

4.1 Appearance: The product surface shall be free from defects, dirt, cracks and mechanical damage.

Contacts shall be free from rust, oxidation or plating peeling.

4.2 Appearance and dimensions shall comply with the requirements of product drawings.

4.3 Exchangeable: Exchangeable with same specification products.

### 5. Materials

Component	Material Specification	Color
Housing	PBT (UL94V-0)	Gray
Lock Lever	PBT (UL94V-0)	Gray
Terminal	Copper Alloy(Gold flash)	-

**6. Test Requirements and Procedures Summary**

Serial No.	Item	Test Method	Technical Requirements
1	Examination of Product	Visual inspection	Meet the drawing requirements, no damage or abnormality in visual appearance
Electrical Requirement			
2	Contact Resistance	A maximum voltage of 20mV and maximum current of 10mA are applied to the Mate connector. (EIA-364-23C)	Contact Resistance $\leq 15m\Omega$
3	Insulation Resistance	Apply 500V DC(rms) for 1 minute between adjacent contacts to measure the insulation resistance. (EIA-364-21B)	Insulation Resistance $\geq 1000M\Omega$
4	Dielectric Withstanding Voltage	Apply 500V AC(rms) for 1 minute and the leakage current shall not exceed 0.5mA to the adjacent terminal and ground of the mate connectors. (EIA-364-20A)	No flashover or insulation breakdown
Mechanical Characteristics			
5	Retention Force for Pin	Exerts a force on the pin end at a rate per Minute $25\pm 3mm$ until the needle exit Seat pull-out force.	Retention Force $\geq 1.0Kgf/Pin$
Environmental Performance			

6	Durability	Mate connectors up 10 cycles at a Maximum rate of 10 cycles per minute prior to environmental test. (EIA-364-09C)	Contact Resistance ≤ 15mΩ;
7	Temperature	Mate connector measure the temperature rise of contact when the maximum rated current is passed. (EIA-364-70B)	Δ 30°C Max
8	Random Vibration	Mated connectors subjected to vibration conditions: 10~55~10Hz, amplitude 1.5mm, 2h per axis, current applied. (EIA-364-28E)	Appearance: No damage; Current Discontinuity ≤ 1ms; Contact Resistance ≤ 15mΩ;
9	Shock	490m/s <sup>2</sup> {50G}, 3 strokes in each X.Y.Z. axes. (EIA-364-27B)	Appearance: No damage; Current Discontinuity ≤ 1ms; Contact Resistance ≤ 15mΩ;
10	Thermal Aging	Mate connector exposed to the condition of 105±2°C for 96 hours; Then store at room temperature for 1 to 2 hours. (EIA-364-17B)	Appearance: No damage; Contact Resistance ≤ 15mΩ;
11	Cold Resistance	Mate connector exposed to the condition of -40±2°C for 96 hours; Then store at room temperature for 1 to 2 hours. (EIA-364-59A)	Appearance: No damage; Contact Resistance ≤ 15mΩ;
12	Humidity-Temperature Cycle	Temperature (40±2) °C, relative humidity 90~95% for 96 h; after the test. (EIA-364-31B)	Appearance: No damage; contact resistance ≤ 15mΩ; insulation resistance ≥ 1000MΩ; No flashover or insulation breakdown;

13	Temperature cycling	One cycle consists of -55±3°C 30min, room temp 10-15min 85±3°C 30min, room temp 10-15min Total cycle :5cycle. (EIA-364-32D)	Appearance: No damage; Contact Resistance ≤ 15mΩ;
14	Salt Spray	Salt concentration: 5%, temperature: (35±2) °C, test time: (24±2) h; after the test, rinse residual salt with clean water, wipe dry before measurement. (EIA-364-26B)	Appearance: no damage