

A





B

C

D

E

F



Long Pin position: F1, F3, F5, F7, F9
G2, G4, G6, G8, G10
Short Pin for other positions

Recommended P.C.Board Layout
Tolerances: ± 0.05

REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

SPECIFICATIONS

Electrical

Current Rating: 0.5A

Voltage Rating: 250V AC(rms)/DC

Contact Resistance: 35 mΩ Max(initial) $\Delta=10$ mΩ Max(After test)

Insulation Resistance: 1000 MΩ Min @500V DC

Withstanding Voltage: 500V AC r.m.s

Operating Temperature: $-55^{\circ}\text{C}\sim+105^{\circ}\text{C}$

Material and plating

Housing: LCP (UL 94V-0)

Contacts: Copper alloy/Selective gold plated
on contact area and matte tin plated on tails

Mechanical Performance

Insertion Force: 0.5N/PIN max.

Withdrawal Force: 0.15N/PIN min.

Mechanical Durability: 200 cycles.

*Date Code: YYWW

Week
Year

Ordering Information

FBP 200 04 — M 120 S 7 XX 3 NA K
1 2 3 4 5 6 7 8 9 10 11

1	Category	2	Series Number	3	Distinction No.	4	Gender	5	Circuits	6	Entry Angle
	FBP—High speed Backplane connector		200—Pitch2.0mm		04		M—Male		120		S—180° Vertical
7	Plating	8	Thickness of Plating	9	Material—Resin	10	Color—Resin	11	Packaging		
	7—Selective gold plated on contact area and matte tin plated on tails		00—Gold flash 01—0.025μm 03—0.075μm Custom plate available		3—LCP		NA—Natural		K—Tray		

 THIRD ANGLE PROJECTION		GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY LEO	DATE 21/JUL/22	PART NO. FBP20004—M120S7XX3XXK	ITEM NO. FBP20004	 Building Technology Cornerstone	
		GB 1804—m	X.* ±5°	CHECKED BY	DATE	TITLE			
DESIGN UNITS METRIC		30~120 ±0.30	X.X* ±2°	GISELLE	21/JUL/22	High speed Backplane connector 4 Pair Pitch 2.0mm Male(Press fit) 12.5Gbps		REV 0	SHEET NO. 1/2
		6~30 ±0.20	X.XX* ±1°	DRAWN BY	DATE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
SCALE 2:1	SIZE A4	0~6 ±0.10	X.XXX* ±0.5°	MATT	21/JUL/22				

A

B

C

D

E

F

A

B



C

D

E

F

REV	LOCATIONS	DESCRIPTION	DATE	REVISED	APPD



Detail A
Scale 5:1

Recommended P.C.Board Layout
Tolerances: ±0.05

<div></div> <div>THIRD ANGLE PROJECTION</div>		GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY LEO	DATE 21/JUL/22	PART NO. FBP20004—M120S7XX3XXK	ITEM NO. FBP20004	<div></div> <div>Building Technology Cornerstone</div>	
		GB 1804—m	X° ±5°	CHECKED BY	DATE	TITLE			
DESIGN UNITS METRIC		30~120 ±0.30	X.X° ±2°	GISELLE	21/JUL/22	High speed Backplane connector 4 Pair Pitch 2.0mm Male(Press fit) 12.5Gbps			
		6~30 ±0.20	X.XX° ±1°						
SCALE 2:1	SIZE A4	0~6 ±0.10	X.XXX° ±0.5°	DRAWN BY MATT	DATE 21/JUL/22	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
						REV 0		SHEET NO. 2/2	