



REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

WIRING CHART		
P1	P2	COLOR
1	1	RED
2	2	GRAY
3	3	GRAY
4	4	GRAY

•	•	•
•	•	•
•	•	•
28	28	GRAY
29	29	GRAY
30	30	GRAY

- ELECTRICAL**
- Withstanding Voltage: DC 300V
 - Conduction impedance: 3Ω (MAX)
 - Insulation Resistance: 10MΩ (MIN)

- PACKING SPECIFICATION**
- 20pcs/Bundle,100pcs/Bag
 - "*"as the key size control

- NOTES**
- This product must meet UL486A-1991mechanical performance.
 - This product must meet 2011/65/EU ROHS compliance.
 - Cable assembly to be tested 100% for continuity and polarity.

2	UL2651 #28 30C Pitch:1.27 Grey
1	IDC 2.54mm (3 Assemblies) Butterfly Buckle ,30Circuits:ID25407-304K6K
NO.	SPECIFICATION

 THIRD ANGLE PROJECTION		GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY	DATE	PART NO.	ITEM NO.	 Leader Of Industry
DESIGN UNITS Metric		X.±0.30	X.°±5°	FRANK	7/JUN/21	FCW003-00000002-00	FCW003	
SCALE 5:1		X.XX±0.20	X.X°±2°	CHECKED BY	DATE	TITLE		
SIZE A4		X.XXX±0.10	X.XX°±1°	CHERRY	7/JUN/21	IDC Cable		REV 0
X.XXX±0.10 X.XX°±0.5°		DRAWN BY JOE		DATE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S,Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		SHEET NO. 1/1	