



REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

ELECTRICAL

1. Withstanding Voltage: DC 300V
2. Conduction impedance: 3Ω (MAX)
3. Insulation Resistance: $10M\Omega$ (MIN)

PACKING SPECIFICATION

1. 1pcs/Bundle,100pcs/Bag
- 2."*"as the key size control

NOTES

- 1.This product must meet UL486A-1991mechanical performance.
- 2.This product must meet 2011/65/EU ROHS compliance.
- 3.Cable assembly to be tested 100% for continuity and polarity.

3	Black Heat Shink Tube \varnothing 3.5mm R-4HA-12
2	Coaxial Cable:RG-316 Brown
1	SMA Connector Male,Gold Plated
NO.	SPECIFICATION

		GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY	DATE	PART NO.	ITEM NO.	 Leader Of Industry
DESIGN UNITS Metric		X.±0.30	X.°±5°	FRANK	3/JUN/21	FCW018-000012	FCW018	
SCALE SIZE 5:1 A4		X.XX±0.20	X.X°±2°	CHECKED BY	DATE	RF CABLE		
		X.XXX±0.10	X.XX°±1°	CHERRY	3/JUN/21			REV 1
		X.XXX±0.10	X.XXX°±0.5°	DRAWN BY	DATE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S,Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
				JOE	3/JUN/21			