

REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

SPECIFICATIONS

Electrical

Current Rating: 2A AC(rms)/DC

Contact Resistance: 20 mΩ Max.

Insulation Resistance: 1000 MΩ Min.

Withstanding Voltage: 1000V AC r.m.s



Temperature Range—Operating: −55°C~+105°C

Material and Plating

Housing: PBT (UL 94V-0)

Contacts: Brass/ Selective gold on contact area,
Matte-tin on tail

Code	No. of Contacts	Contact Arrangement
A	48	
D	32	
F	16	



Recommended P.C.Board Layout
General Tolerances: ±0.05mm

Ordering Information

FES 254 23 — M T XX S 3 XX 1 GY K X—X
1 2 3 4 5 6 7 8 9 10 11 12 13 14

1 Category FES—European style socket	2 Series Number 254—Pitch 2.54mm	3 Distinction No. 23	4 Type M—Male	5 Row Option T—Three Row	6 Circuits XX	7 Entry Angle S—180° Vertical
8 Plating 3—Gold on contact Matte-tin on tail	9 Thickness of Gold Plating 01—1μ" 10—10μ" 15—15μ" Custom plate available	10 Material—Resin 1—PBT	11 Color—Resin GY—Grey	12 Packaging K—Tray	13 Code A—A B—B C—C	14 Type H=5.0mm—A H=13.0mm—B H=17.0mm—C

 THIRD ANGLE PROJECTION		GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY LEO	DATE 14/FEB/23	PART NO. FES25423-MTXXS3XX1GYKX-X	ITEM NO. FES25423	 Building Technology Cornerstone	
DESIGN UNITS METRIC				CHECKED BY GISELLE	DATE 14/FEB/23	TITLE European style socket Pitch 2.54mm 180°Vertical(Male)			
SCALE 5:1	SIZE A4	X. ±0.30	X.* ±5°	DRAWN BY CHERRY	DATE 14/FEB/23	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		REV 0	SHEET NO. 1/1
		X.X ±0.20	X.X* ±2°						
		X.XX ±0.15	X.XX* ±1°						
		X.XXX ±0.10	X.XXX* ±0.5°						