



REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD





SPECIFICATIONS
Electrical
Current Rating: 5.6A AC(rms)/DC
Contact Resistance: 20 mΩ Max.
Insulation Resistance: 1000 MΩ Min@500V DC.
Withstanding Voltage: 1000V AC r.m.s
Temperature Range-Operating: -55°C~+105°C
Material and Plating
Housing: PBT (UL 94V-0)
Contacts: Brass/ Selective gold on contact area, tin on tail, nickel plated under overall.
*Date Code: YYWW
Week
Year





Recommended P.C.Board Layout
General Tolerances: ±0.05mm

Ordering Information

FES	508	03	—	F	T	48	S	X	XX	1	XX	K
1	2	3		4	5	6	7	8	9	10	11	12

1	Category	2	Series Number	3	Distinction No.	4	Type	5	Row Option	6	Circuits	7	Entry Angle
	FES-European style socket		508-Pitch5.08mm		03		F-Female		T-Three Row		48		S-180° Vertical
8	Plating	9	Thickness of Gold Plating	10	Material-Resin	11	Color-Resin	12	Packaging				
	3-Gold on contact bright tin on tail		02-0.05μm		1-PBT		GY-Grey		K-Tray				

THIRD ANGLE PROJECTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY	DATE	PART NO.	ITEM NO.	TXGA Building Technology Cornerstone
			LEO	06/APR/23	FES50803-FT48S3XX1XXK	FES50803	
DESIGN UNITS METRIC	X. ±0.50	X.° ±5°	CHECKED BY	DATE	TITLE European style socket Female Pitch 5.08mm 180° Vertical (DIP)		
	X.X ±0.30	X.X° ±2°	GISELLE	06/APR/23		REV 0	SHEET NO. 1/1
SCALE 1.5:1	X.XX ±0.20	X.XX° ±1°	DRAWN BY	DATE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
SIZE A4	X.XXX ±0.10	X.XXX° ±0.5°	MATT	06/APR/23			