


REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD








SPECIFICATIONS
Electrical
Current Rating: 5A AC(rms)/DC
Contact Resistance: 30 mΩ Max.
Insulation Resistance: 1000 MΩ Min@500V DC.
Withstanding Voltage: 1000V AC r.m.s
Temperature Range-Operating: -55°C~+105°C
Material and Plating
Housing: PBT (UL 94V-0)
Contacts: Brass/Gold Plated/Selective gold on contact area, tin on tail, nickel plated under overall.
*Date Code: YYWW
Week
Year

Ordering Information

FES	508	06	—	M	F	64	S	X	XX	1	XX	K
1	2	3		4	5	6	7	8	9	10	11	12

1	Category	2	Series Number	3	Distinction No.	4	Type	5	Row Option	6	Circuits	7	Entry Angle
	FES-European style socket		508-Pitch5.08mm		06		M-Male		F-Four rows		64		S-180° Vertical

8	Plating	9	Thickness of Gold Plating	10	Material-Resin	11	Color-Resin	12	Packaging
	1-Gold Plated		02-0.05μm		1-PBT		NA-Natural		K-Tray



Recommended P.C.Board Layout
General Tolerances: ±0.05mm

THIRD ANGLE PROJECTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY LEO	DATE 06/APR/23	PART NO. FES50806-MF64SXXX1XXK	ITEM NO. FES50806
	X. ±0.50	X.° ±5°				
DESIGN UNITS METRIC	X.X ±0.30	X.X° ±2°	CHECKED BY GISELLE	DATE 06/APR/23	TITLE European style socket Male Pitch 5.08mm 180° Vertical (DIP)	
	X.XX ±0.20	X.XX° ±1°				
SCALE 1.5:1	SIZE A4	X.XXX ±0.10	X.XXX° ±0.5°	DRAWN BY MATT	DATE 06/APR/23	

TXGA Building Technology Cornerstone

REV 0 | SHEET NO. 1/1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION