





| REV | LOCATIONS | DESCRIPTION | DATE | REVISED | APPD |
|-----|-----------|-------------|------------|---------|------|
| 1 | △ | Size change | 15/Sept/25 | NICK | LEO |

Electrical

Current Rating: 1A AC(rms)/DC
Voltage Rating: 250V AC(rms)/DC
Contact Resistance: 20 mΩ Max
Insulation Resistance: 1000 MΩ MIN
Withstanding Voltage: 500V AC r.m.s
Temperature Range—Operating: -40°C~+85°C

Material and Plating

Housing: PA6T(UL 94V-0)
Contact Pin: Phosphor Bronze
Plating: Gold Plated



Recommended P.C.Board Layout

Ordering Information

FFH 127 12 — S XX B X XX 4 K6 K
1 2 3 4 5 6 7 8 9 10 11



| | | | | | | | | | | | |
|---|---|---|---|---|--------------------------|----|----------------------------|----|---------------------|---|----------------------------|
| 1 | Category FFH—Female Header | 2 | Series Number 127—Pitch1.27mm | 3 | Distinction No. 12 | 4 | Row Option S—Single row | 5 | Circuits XX | 6 | Entry Angle B—90° Angle |
| 7 | Plating 1—Gold Plated 3—Selective gold on contact area, tin on tail | 8 | Thickness of Plating 00—Gold Flash 05—5μ" Custom plate available | 9 | Material—Resin 4—PA6T | 10 | Color—Resin K6—Black | 11 | Packaging K—Tray | | |

| | | | | | | | | |
|----------------------------|---------------------------------------|-------------------------------------|---------------------|----------------------|----------------------------------|--|------------------------|-------|
| THIRD ANGLE PROJECTION | GENERAL TOLERANCES (UNLESS SPECIFIED) | | APPROVE BY FRANK | DATE 10/JUL/13 | PART NO. FFH12712-SXXBXXX4K6K | ITEM NO. FFH12712 | Leader Of Industry | |
| | DESIGN UNITS Inch (metric) | X.±.012(0.30) X.X±.008(0.20) | X.±5° .X±2° | CHECKED BY CHERRY | DATE 10/JUL/13 | TITLE Board to Board (Female Header) Pitch 1.27mm 90° Angle (DIP) | | REV 1 |
| SCALE 5:1 | SIZE A4 | X.XX±.006(0.15) X.XXX±.004(0.10) | .XX±1° .XXX±0.5° | DRAWN BY JACOB | DATE 10/JUL/13 | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | |

1 2 3 4 5 6 7 8

| REV | LOCATIONS | DESCRIPTION | DATE | REVISER | APPD |
|-----|-----------|-------------|------|---------|------|
| | | | | | |

| Circuits (n) | Part No. | Dimensions(in/mm) | | Circuits (n) | Part No. | Dimensions(in/mm) | |
|--------------|----------------------|-------------------|--------------|--------------|----------------------|-------------------|--------------|
| | | A | B | | | A | B |
| 2 | FFH12712-S02BXXX4K6K | .050(1.27) | .114(2.89) | 22 | FFH12712-S22BXXX4K6K | 1.050(26.67) | 1.114(28.29) |
| 3 | FFH12712-S03BXXX4K6K | .100(2.54) | .164(4.16) | 23 | FFH12712-S23BXXX4K6K | 1.100(27.94) | 1.164(29.56) |
| 4 | FFH12712-S04BXXX4K6K | .150(3.81) | .214(5.43) | 24 | FFH12712-S24BXXX4K6K | 1.150(29.21) | 1.214(30.83) |
| 5 | FFH12712-S05BXXX4K6K | .200(5.08) | .264(6.70) | 25 | FFH12712-S25BXXX4K6K | 1.200(30.48) | 1.264(32.10) |
| 6 | FFH12712-S06BXXX4K6K | .250(6.35) | .314(7.97) | 26 | FFH12712-S26BXXX4K6K | 1.250(31.75) | 1.314(33.37) |
| 7 | FFH12712-S07BXXX4K6K | .300(7.62) | .364(9.24) | 27 | FFH12712-S27BXXX4K6K | 1.300(33.02) | 1.364(34.64) |
| 8 | FFH12712-S08BXXX4K6K | .350(8.89) | .414(10.51) | 28 | FFH12712-S28BXXX4K6K | 1.350(34.29) | 1.414(35.91) |
| 9 | FFH12712-S09BXXX4K6K | .400(10.16) | .464(11.78) | 29 | FFH12712-S29BXXX4K6K | 1.400(35.56) | 1.464(37.18) |
| 10 | FFH12712-S10BXXX4K6K | .450(11.43) | .514(13.05) | 30 | FFH12712-S30BXXX4K6K | 1.450(36.83) | 1.514(38.45) |
| 11 | FFH12712-S11BXXX4K6K | .500(12.70) | .564(14.32) | 31 | FFH12712-S31BXXX4K6K | 1.500(38.10) | 1.564(39.72) |
| 12 | FFH12712-S12BXXX4K6K | .550(13.97) | .614(15.59) | 32 | FFH12712-S32BXXX4K6K | 1.550(39.37) | 1.614(40.99) |
| 13 | FFH12712-S13BXXX4K6K | .600(15.24) | .664(16.86) | 33 | FFH12712-S33BXXX4K6K | 1.600(40.64) | 1.664(42.26) |
| 14 | FFH12712-S14BXXX4K6K | .650(16.51) | .714(18.13) | 34 | FFH12712-S34BXXX4K6K | 1.650(41.91) | 1.714(43.53) |
| 15 | FFH12712-S15BXXX4K6K | .700(17.78) | .764(19.40) | 35 | FFH12712-S35BXXX4K6K | 1.700(43.18) | 1.764(44.80) |
| 16 | FFH12712-S16BXXX4K6K | .750(19.05) | .814(20.67) | 36 | FFH12712-S36BXXX4K6K | 1.750(44.45) | 1.814(46.07) |
| 17 | FFH12712-S17BXXX4K6K | .800(20.32) | .864(21.94) | 37 | FFH12712-S37BXXX4K6K | 1.800(45.72) | 1.864(47.34) |
| 18 | FFH12712-S18BXXX4K6K | .850(21.59) | .914(23.21) | 38 | FFH12712-S38BXXX4K6K | 1.850(46.99) | 1.914(48.61) |
| 19 | FFH12712-S19BXXX4K6K | .900(22.86) | .964(24.48) | 39 | FFH12712-S39BXXX4K6K | 1.900(48.26) | 1.964(49.88) |
| 20 | FFH12712-S20BXXX4K6K | .950(24.13) | 1.014(25.75) | 40 | FFH12712-S40BXXX4K6K | 1.950(49.53) | 2.014(51.55) |
| 21 | FFH12712-S21BXXX4K6K | 1.000(25.40) | 1.064(27.02) | | | | |

| | | | | | | | | |
|---|--|--|--|----------------------|--|---|---|---------------|
|  THIRD ANGLE PROJECTION | GENERAL TOLERANCES (UNLESS SPECIFIED) | | APPROVE BY FRANK | DATE 10/JUL/13 | PART NO. FFH12712-SXXBXXX4K6K | ITEM NO. FFH12712 |  Leader Of Industry | |
| | DESIGN UNITS Inch (metric) | X.±.012(0.30) X.X±.008(0.20) X.XX±.006(0.15) X.XXX±.004(0.10) | X.±5' .X'±2' .XX'±1' .XXX'±0.5' | CHECKED BY CHERRY | DATE 10/JUL/13 | TITLE Board to Board (Female Header) Pitch 1.27mm 90° Angle (DIP) | | |
| SCALE 5:1 | SIZE A4 | | DRAWN BY JACOB | DATE 10/JUL/13 | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | REV 1 | SHEET NO. 2/2 |

1 2 3 4 5 6 7 8

1 2 3 4 5 6 7 8





| REV | LOCATIONS | DESCRIPTION | DATE | REVISER | APPD |
|-----|-----------|--------------|-----------|---------|--------|
| 1 | △ | Size changes | 28/JUL/20 | KATE | CHERRY |

Electrical

Current Rating: 1A AC(rms)/DC
 Voltage Rating: 250V AC(rms)/DC
 Contact Resistance: 20 mΩ Max
 Insulation Resistance: 1000 MΩ MIN
 Withstanding Voltage: 500V AC r.m.s
 Temperature Range—Operating: -40°C ~ +85°C

Material and Plating

Housing: PA6T(UL 94V-0)
 Contact Pin: Phosphor Bronze
 Plating: Gold Plated



Recommended P.C.Board Layout

Ordering Information

FFH 127 12 — D XX B X XX 4 K6 K
 1 2 3 4 5 6 7 8 9 10 11



| | | | | | | | | | | | |
|---|--|---|---|---|-----------------|----|--------------|----|-----------|---|-------------|
| 1 | Category | 2 | Series Number | 3 | Distinction No. | 4 | Row Option | 5 | Circuits | 6 | Entry Angle |
| | FFH—Female Header | | 127—Pitch1.27mm | | 12 | | D—Double Row | | XX | | B—90° Angle |
| 7 | Plating | 8 | Thickness of Plating | 9 | Material—Resin | 10 | Color—Resin | 11 | Packaging | | |
| | 1—Gold Plated 3—Selective gold on contact area, tin on tail | | 00—Gold Flash 05—5μ" Custom plate available | | 4—PA6T | | K6—Black | | K—Tray | | |

| | | | | | | | |
|-------------------------------|---------------------------------------|------------|------------|-----------|--|---------------------|------------------------|
| THIRD ANGLE PROJECTION | GENERAL TOLERANCES (UNLESS SPECIFIED) | | APPROVE BY | DATE | PART NO. | ITEM NO. | Leader Of Industry |
| | X.±.012(0.30) | X.±5' | FRANK | 10/JUL/13 | FFH12712-DXXBXXX4K6K | FFH12712 | |
| DESIGN UNITS Inch (metric) | X.X±.008(0.20) | .X'±2' | CHECKED BY | DATE | TITLE | REV 1 SHEET NO. 1/2 | |
| SCALE 5:1 | X.XX±.006(0.15) | .XX'±1' | DRAWN BY | DATE | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | |
| SIZE A4 | X.XXX±.004(0.10) | .XXX'±0.5' | JACOB | 10/JUL/13 | | | |

1 2 3 4 5 6 7 8

| REV | LOCATIONS | DESCRIPTION | DATE | REVISER | APPD |
|-----|-----------|-------------|------|---------|------|
| | | | | | |

| Circuits (n) | Part No. | Dimensions(in/mm) | | Circuits (n) | Part No. | Dimensions(in/mm) | |
|-----------------|----------------------|-------------------|--------------|-----------------|----------------------|-------------------|--------------|
| | | A | B | | | A | B |
| 4 | FFH12712-D04BXXX4K6K | .050(1.27) | .114(2.89) | 44 | FFH12712-D44BXXX4K6K | 1.050(26.67) | 1.114(28.29) |
| 6 | FFH12712-D06BXXX4K6K | .100(2.54) | .164(4.16) | 46 | FFH12712-D46BXXX4K6K | 1.100(27.94) | 1.164(29.56) |
| 8 | FFH12712-D08BXXX4K6K | .150(3.81) | .214(5.43) | 48 | FFH12712-D48BXXX4K6K | 1.150(29.21) | 1.214(30.83) |
| 10 | FFH12712-D10BXXX4K6K | .200(5.08) | .264(6.70) | 50 | FFH12712-D50BXXX4K6K | 1.200(30.48) | 1.264(32.10) |
| 12 | FFH12712-D12BXXX4K6K | .250(6.35) | .314(7.97) | 52 | FFH12712-D52BXXX4K6K | 1.250(31.75) | 1.314(33.37) |
| 14 | FFH12712-D14BXXX4K6K | .300(7.62) | .364(9.24) | 54 | FFH12712-D54BXXX4K6K | 1.300(33.02) | 1.364(34.64) |
| 16 | FFH12712-D16BXXX4K6K | .350(8.89) | .414(10.51) | 56 | FFH12712-D56BXXX4K6K | 1.350(34.29) | 1.414(35.91) |
| 18 | FFH12712-D18BXXX4K6K | .400(10.16) | .464(11.78) | 58 | FFH12712-D58BXXX4K6K | 1.400(35.56) | 1.464(37.18) |
| 20 | FFH12712-D20BXXX4K6K | .450(11.43) | .514(13.05) | 60 | FFH12712-D60BXXX4K6K | 1.450(36.83) | 1.514(38.45) |
| 22 | FFH12712-D22BXXX4K6K | .500(12.70) | .564(14.32) | 62 | FFH12712-D62BXXX4K6K | 1.500(38.10) | 1.564(39.72) |
| 24 | FFH12712-D24BXXX4K6K | .550(13.97) | .614(15.59) | 64 | FFH12712-D64BXXX4K6K | 1.550(39.37) | 1.614(40.99) |
| 26 | FFH12712-D26BXXX4K6K | .600(15.24) | .664(16.86) | 66 | FFH12712-D66BXXX4K6K | 1.600(40.64) | 1.664(42.26) |
| 28 | FFH12712-D28BXXX4K6K | .650(16.51) | .714(18.13) | 68 | FFH12712-D68BXXX4K6K | 1.650(41.91) | 1.714(43.53) |
| 30 | FFH12712-D30BXXX4K6K | .700(17.78) | .764(19.40) | 70 | FFH12712-D70BXXX4K6K | 1.700(43.18) | 1.764(44.80) |
| 32 | FFH12712-D32BXXX4K6K | .750(19.05) | .814(20.67) | 72 | FFH12712-D72BXXX4K6K | 1.750(44.45) | 1.814(46.07) |
| 34 | FFH12712-D34BXXX4K6K | .800(20.32) | .864(21.94) | 74 | FFH12712-D74BXXX4K6K | 1.800(45.72) | 1.864(47.34) |
| 36 | FFH12712-D36BXXX4K6K | .850(21.59) | .914(23.21) | 76 | FFH12712-D76BXXX4K6K | 1.850(46.99) | 1.914(48.61) |
| 38 | FFH12712-D38BXXX4K6K | .900(22.86) | .964(24.48) | 78 | FFH12712-D78BXXX4K6K | 1.900(48.26) | 1.964(49.88) |
| 40 | FFH12712-D40BXXX4K6K | .950(24.13) | 1.014(25.75) | 80 | FFH12712-D80BXXX4K6K | 1.950(49.53) | 2.014(51.55) |
| 42 | FFH12712-D42BXXX4K6K | 1.000(25.40) | 1.064(27.02) | | | | |

| | | | | | | | | |
|---|--|------------------|---------------------|--|----------------------------------|---|---|---------------|
|  THIRD ANGLE PROJECTION | GENERAL TOLERANCES (UNLESS SPECIFIED) | | APPROVE BY FRANK | DATE 10/JUL/13 | PART NO. FFH12712-DXXBXXX4K6K | ITEM NO. FFH12712 |  Leader Of Industry | |
| | DESIGN UNITS Inch (metric) | X.±.012(0.30) | X'±5' | CHECKED BY CHERRY | DATE 10/JUL/13 | TITLE Board to Board (Female Header) Pitch 1.27mm 90° Angle (DIP) | | |
| | | X.XX±.008(0.20) | .X'±2' | DRAWN BY JACOB | DATE 10/JUL/13 | REV 1 | | SHEET NO. 2/2 |
| | | X.XX±.006(0.15) | .XX'±1' | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | | | |
| SCALE 5:1 | SIZE A4 | X.XXX±.004(0.10) | .XXX'±0.5' | | | | | |