



REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD



SPECIFICATIONS

Electrical

Current Rating: 0.5A AC(rms)/DC
Voltage Rating: 40V AC(rms)/DC
Contact Resistance: 30 mΩ Max
Insulation Resistance: 100 MΩ Min
Withstanding Voltage: 500V AC r.m.s

Mechanical

Mating force: 4.4KG.F Max
Retention force: 0.5–4.0KG.F
Durability: 5000 cycles Min.

Environmental



Operating Temperature: -25°C~+85°C

Material and plating


Housing: LCP (UL 94V-0), Black
Contacts: Copper Alloy/Gold plated on contact, Matte Tin plated on tail
Shell: Copper Alloy/Nikel plated

Recommended P.C.Board Layout

General Tolerances: ±0.05mm



Pin	Signal Assignment	Pin	Signal Assignment
1	TMDS Data2+	2	TMDS Data2 Shield
3	TMDS Data2-	4	TMDS Data1+
5	TMDS Data1 Shield	6	TMDS Data1-
7	TMDS Data0+	8	TMDS Data0 Shield
9	TMDS Data0-	10	TMDS Clock+
11	TMDS Clock Shield	12	TMDS Clock-
13	CEC	14	Reserved (N.C. on device)
15	SCL	16	SDA
17	DDC/CEC Ground	18	+5V Power
19	Hot Plug Detect	/	/









<p>THIRD ANGLE PROJECTION</p>	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY FRANK	DATE 15/AUG/22	PART NO. FHD33-FDB700BKM	ITEM NO. FHD33
	X.±0.30	X.±5°	CHECKED BY CHERRY	DATE 15/AUG/22	TITLE HDMI A/F 90°(DIP)	
	X.XX±0.15	.XX'±1"	DRAWN BY QING	DATE 15/AUG/22		
	X.XXX±0.10	.XXX'±0.5"			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
DESIGN UNITS (metric)					REV 0	SHEET NO. 1/2
SCALE 5:1	SIZE A4					



REV 0	SHEET NO. 1/2
-------	---------------

REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

- Note:
- 1.10 sprocket hole cumulative tolerance ± 0.2
 2. Carrier camber is within 1.0mm in 250mm
 3. Material: Clear conductive polystyrene Alloy 100% recyclable
 4. All dimensions meet EIA-481-3 requirements
 5. Peel off force of cover tape & carrier tape: 20g~130g (0.2N~1.3N)
 6. Component load per 13" reel: 500 pcs



 THIRD ANGLE PROJECTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY	DATE	PART NO.	ITEM NO.	 Leader Of Industry		
	X. ± 0.30	X. $\pm 5^{\circ}$	FRANK	15/AUG/22	FHD33-FDB700BKM	FHD33			
	DESIGN UNITS (metric)	X.X ± 0.20	X. $\pm 2^{\circ}$	CHECKED BY	DATE	TITLE		REV 0	SHEET NO. 2/2
	SCALE 5:1	SIZE A4	X.XX ± 0.15	CHERRY	15/AUG/22	HDMI A/F 90(DIP)			
		X.XXX ± 0.10	.XX $\pm 1^{\circ}$	DRAWN BY	DATE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
		X.XXX ± 0.10	.XXX $\pm 0.5^{\circ}$	QING	15/AUG/22				