






REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD
1	▲	Structura & Sizel changes	02/AUG/23	MATT	LEO



Section A-A




Electrical
 Temperature Range—Operating: -25°C~+85°C
 Material
 Housing: PA66(UL 94V-0)
 Applicable Terminal: FT15005

Circuits (n)	Part No.	Dimensions(in/mm)	
		A	B ▲
2	FHG15004-S02M2W1B	.059(1.50)	.142(3.60)
3	FHG15004-S03M2W1B	.118(3.00)	.201(5.10)
4	FHG15004-S04M2W1B	.177(4.50)	.260(6.60)
5	FHG15004-S05M2W1B	.236(6.00)	.319(8.10)
6	FHG15004-S06M2W1B	.295(7.50)	.378(9.60)
7	FHG15004-S07M2W1B	.354(9.00)	.437(11.10)
8	FHG15004-S08M2W1B	.413(10.50)	.496(12.60)
9	FHG15004-S09M2W1B	.472(12.00)	.555(14.10)
10	FHG15004-S10M2W1B	.531(13.50)	.614(15.60)
11	FHG15004-S11M2W1B	.591(15.00)	.673(17.10)
12	FHG15004-S12M2W1B	.650(16.50)	.732(18.60)
13	FHG15004-S13M2W1B	.709(18.00)	.791(20.10)
14	FHG15004-S14M2W1B	.768(19.50)	.850(21.60)
15	FHG15004-S15M2W1B	.827(21.00)	.909(23.10)


Ordering Information

FHG 150 04 — S XX M 2 W1 B
 1 2 3 4 5 6 7 8 9

1	Category FHG—Housing	2	Series Number 150—Pitch1.50mm	3	Distinction No. 04	4	Row Option S—Single row		
5	Circuits XX	6	Type M—Male	7	Material—Resin 2—PA66	8	Color—Resin W1—White	9	Packaging B—PE Bag



Recommended P.C.Board Layout

THIRD ANGLE PROJECTION		GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY	DATE	PART NO.	ITEM NO.	 Leader Of Industry
DESIGN UNITS Inch (metric)	X.±.012(0.30)	X:±5'	FRANK	DATE	04/SEP/19	FHG15004-SXXM2W1B	FHG15004	
	X.X±.008(0.20)	.X'±2'						CHECKED BY
SCALE 5:1	X.XX±.006(0.15)	.XX'±1'	DRAWN BY	DATE	04/SEP/19	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
	X.XXX±.004(0.10)	.XXX'±0.5'						