

REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

A




B

C

D

E

F



SPECIFICATION

Technical Parameters

No. of contact: 12/2+PE

Power area:

Rated current: 40A

Rated voltage: 690V

Rated impulse voltage: 8KV

Contact resistance: 1mΩ MAX

Wire gauge: 1.5–6.0mm²(16–10 AWG)

Signal area:

Rated current: 10A

Rated voltage: 250V

Rated impulse voltage: 4KV

Contact resistance: 3mΩ MAX

Power contacts: 0.14–2.5mm²(26–14 AWG)

Rated voltage acc.to UL/CSA: 600/300V

Insulation resistance: 10¹⁰Ω MIN

Temperature range: –40°C~+125°C

Pollution degree: 3

Mechanical

Connection method: Riveting

Durability: 500 cycles MIN

Material and Plating

Insulators: PC(UL 94V–0),Light grey

A

B

C

D

E

F

 THIRD ANGLE PROJECTION		GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY LEO	DATE 30/JUN/21	PART NO. FHK00008–F0140GYR0	ITEM NO. FHK00008	 Building Technology Cornerstone		
DESIGN UNITS mm		X. ±0.30	X.* ±5°	CHECKED BY GISELLE	DATE 30/JUN/21	TITLE Heavy-duty connector HK Insert		REV 0	SHEET NO. 1/1	
SCALE 5:1	SIZE A4	X.XX ±0.15	X.XX° ±1°	DRAWN BY PYD	DATE 30/JUN/21	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				
		X.XXX ±0.10	X.XXX° ±0.5°							