REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

SPECIFICATIONS

No. of contact: 8
Rated current: 1A
Rated voltage: 50V
Rated impulse voltage: 0.8kV
Pollution degree: 3
Rated voltage acc.to UL: <30V
Transmission features: category 6/Class E up to 500 MHz; acc. to ISO/IEC 24 702; ISO/IEC 11 801
Transmissiong rate: 10/100/1000Mbit/10Gbit/s
Insulation resistance: $\geqslant 10^{10}\Omega$
Temperature Range-Operating: -40℃ ~ +85℃
Durability: 500 cycles MIN
Insulators: PC(UL 94V-0),Light grey







THIRD ANGLE PROJECTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY LEO	DATE 05/Jul/21	PART NO. FHM45003-M0000GY00	ITEM NO. FHM45003	TXGA Building Technology Cornerstone
DESIGN UNITS mm	X. ±0.30	X.° ±5°	CHECKED BY GISELLE	DATE 05/Jul/21	TITLE Heavy-duty connector HM Insert		REV 0 / SHEET NO. 1/1
SCALE 5:1 / SIZE A4	X.X ±0.20	X.X° ±2°					
	X.XX ±0.15	X.XX° ±1°	DRAWN BY PYD	DATE 05/Jul/21			
	X.XXX ±0.10	X.XXX° ±0.5°					

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION