


REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD



**SPECIFICATIONS**

**Electrical**  
 Current Rating: 3.0A AC(rms)/DC  
 Voltage Rating: 500V AC(rms)/DC  
 Contact Resistance: 10 mΩ Max  
 Insulation Resistance: 5000 MΩ MIN  
 Withstanding Voltage: 800V AC r.m.s  
 Temperature Range-Operating: -55°C~+125°C

**Mechanical**  
 Durability: 500 Cycles  
 Vibration: Frequency 10~2000Hz, Acceleration 196m/s<sup>2</sup>,  
 Shock: Peak Acceleration 735m/s<sup>2</sup> 11ms.

**Material and Plating**  
 Housing: High-temperature plastic Natural(UL94V-0)  
 Contact Pin: Copper Alloy/Gold Plated  
 Shell: Aluminium alloy/Nickel Plated  
 Seal Pad: Silicone Rubber RED  
 Nut: Stainless steel

**Ordering Information**

FMD0 01 — F 031 B D XX — X X  
 1 2 3 4 5 6 7 8 9

Category	2	Distinction No.	3	Gender	4	Circuits	5	Entry Angle
FMD0-Micro-D Connector	01	F-Female	31	B-90° Angle				
Assembly Layout	6	Color-Resin	7	Type	8	H	9	
D-DIP	NA-Natural	0-Standard	0-H=3					

<p>THIRD ANGLE PROJECTION</p>	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY	DATE	PART NO.	ITEM NO.	<p>Building Technology Cornerstone</p>
	X.X ±0.30	X.X' ±5'	LEO	17/OCT/24	FMD001-F031BDNA-00	FMD001	
	X.X ±0.20	X.X' ±2'	CHECKED BY	DATE	TITLE		
	X.XX ±0.15	X.XX' ±1'	GISELLE	17/OCT/24	Micro-D Connector Pitch 1.27mm Female(DIP)		
SCALE	SIZE	X.XXX ±0.10	X.XXX' ±0.5'	DRAWN BY	DATE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
NTS	A4			HUANG	17/OCT/24		

Recommended P.C.Board Layout  
 General tolerances: ±0.05