



REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

SPECIFICATIONS

Electrical  
Temperature Range—Operating: −55°C~+125°C  
Salt spray: 12h  
Material and Plating  
Screw: Steel / Nickel Plated

 THIRD ANGLE PROJECTION		GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY	DATE	PART NO.	ITEM NO.	 Leader Of Industry	
				FRANK	27/AUG/21	FSM040-10100200-01	FSM040		
DESIGN UNITS Metric		X. ±0.30	X.' ±5'	CHECKED BY	DATE	TITLE  M4-6g Cross Screw		REV 0	SHEET NO. 1/1
		X.X ±0.20	X.X' ±2'	CHERRY	27/AUG/21				
		X.XX ±0.15	X.XX' ±1'	DRAWN BY	DATE				
SCALE 1:1	SIZE A4	X.XXX ±0.10	X.XXX' ±0.5'	MATT	27/AUG/21	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			